

# Tersus

## TC50 Controller

### Overview

The TC50 Controller is a rugged multifunctional data controller with design of 5 inch sunlight readable HD touch screen and an alphanumerical keypad. Equipped with powerful Octa-core processor and android operating system, it is perfect to adapt with Tersus survey software.

With professional IP68 rating, it is robust and reliable for outdoor harsh environment. The large capacity lithium battery guarantees more than 10 hours of field working for a whole day of multiple surveying tasks.

### Key Features

- ✓ 5 inch sunlight readable HD touch screen
- ✓ Octa-core 2.0GHz CPU
- ✓ Android 8.1 operating system
- ✓ 4GB RAM + 64GB ROM
- ✓ 5MP front camera and 13MP rear camera
- ✓ IP68 certified grade, water/shock/dust proof
- ✓ 7000mAh battery
- ✓ Wi-Fi, Bluetooth, NFC, 4G
- ✓ USB Type-C



# Technical Specifications

System		Electrical	
Operating system:	Android 8.1	Battery:	7000mAh 3.8V
CPU:	MT6763 Octa-core 2.0GHz	Battery life:	14 hours
Memory:	4GB RAM + 64GB ROM	Charging time:	<4 hours (fast charge)
External storage:	Micro SD, up to 128GB	Physical	
Display:	5" sunlight-readable capacitive touch screen	Dimension:	207mmx84mmx20mm
Resolution:	1280x720	Weight:	370g (include battery)
Camera:	5MP front , 13MP rear	Environmental	
Flash light:	High light flash LED	Operating Temperature:	-10°C ~ +60°C
		Storage Temperature:	-30°C ~ +70°C
		Humidity:	5% ~ 95%
		Dust-proof & Waterproof:	IP68
Communication		Shock:	1.5m drop onto concrete
Wi-Fi:	IEEE 802.11a/b/g/n 2.4G&5G	Vibration:	MIL-STD-810G, FIG 514.6C-1
Cellular mode:	Dual SIM Dual Standby	Operations	
SIM slot:	2 Micro SIM slots	Power Button:	Power on/off, reboot, forced restart
SIM1 & SIM2:	FDD-LTE B1/B3/B5/B7/B8	Menu Key:	Shows applications that was used recently
	TD-LTE B38/B39/B40/B41	Home Key:	Return to home screen
	TDSCDMA B34/B39	Back Key:	Return to previous screen
	WCDMA B1/B2/B5/B8	APP Key:	Quick start Nuwa application
	CDMA1x/CDMA2000 BC0/BC1	ENTER Key:	Execute the function of confirming in Nuwa application
	GSM B2/B3/B5/B8	aA Key:	Caps lock
Bluetooth:	BT4.1 (BLE)	FN Key:	Switch between numbers & characters
USB:	USB Type-C (supports OTG)	Blue Positioning Key:	Start measurement in the Survey and Stakeout interface of Nuwa application
NFC:	Protocol of ISO14443A/B, ISO15693	Yellow Bulb Key:	Control the screen on and off
	Readable distance 0~5cm		
GNSS:	GPS/GLONASS/BeiDou		
Sensors:	G-Sensor, Compass, Light-Sensor, Gyro		

**Website** | [www.tersus-gnss.com](http://www.tersus-gnss.com)

**Sales Inquiry** | [sales@tersus-gnss.com](mailto:sales@tersus-gnss.com)

**Technical Support** | [support@tersus-gnss.com](mailto:support@tersus-gnss.com)