



## Nuwa Version(2.1.0.5) Release

---

October 15, 2019

### Overview

Tersus GNSS Inc. ("Tersus") is glad to release the Nuwa for GNSS receiver. Nuwa version (2.1.0.5) is available to download at [www.tersus-gnss.com/software/david-receiver](http://www.tersus-gnss.com/software/david-receiver) and support documents are available at [www.tersus-gnss.com/document](http://www.tersus-gnss.com/document).

### Features

- Assists with Bluetooth/USB connection
- Configure base/rover setup
- Visualized interface for receiver operations
- Data management (import/export)

## Change from Previous Versions

Issue	Type	Version
Fixed the crash when connecting devices using Android 9 caused by the API level change.	Bug Fix	2.1.0.5
Fixed the problems that Nuwa is unable to obtain HTTP permissions using Android 9 caused by the API level change, including inability to perform software automatic update and online map display.	Bug Fix	
Added moving direction indicator arrow in stakeout interface.	Enhancement	2.1.0.3
Added the circle display whose radius is equal to the prompt tone distance in stakeout interface.	Enhancement	
The prompt tone in different grades in stakeout interface. When the surveyor is approaching to the point to stake out, Nuwa beeps every 5 seconds. When the surveyor arrives at the point to stake out, Nuwa beeps every 1 second.	Enhancement	
Added the XML format export which supports being imported to EZSurv to post process Stop&Go data.	Enhancement	
Adjusted DXF export, add height coordinate and height annotation. Distinguish layers according to different kinds of annotations and point feature property.	Enhancement	
Added GNSS Linework function. The survey	Enhancement	

Information and related materials are subject to change without notice. ©Copyright 2019 Tersus GNSS Inc.

Technical Support: [support@tersus-gnss.com](mailto:support@tersus-gnss.com) Website: [www.tersus-gnss.com](http://www.tersus-gnss.com)

line will be displayed in survey interface. The survey line allows operations such as delete point, insert point, and continue surveying.		
Change the API level to 28 and re-launch on Google Play.	Bug Fix	
Fixed the issue that the point coordinate saved to the Point database may be wrong in the case of the Base Shift.	Bug Fix	
Fixed incomplete import Stakeout Point selecting all from Survey Point.	Bug Fix	
Fixed the crash issue when turning on location share function for some android devices.	Bug Fix	
Tilt compensation function is available for Oscar Ultimate model.	Enhancement	2.0.1.6
Added elevation stakeout for point stakeout and line stakeout.	Enhancement	
Opened the TCP Client function for the receiver network.	Enhancement	
Solved the problem that conversion from NEH to BLH may be incorrect when there are seven parameters.	Bug Fix	
Solved the problem that selecting the coordinate system from the Coord System List is not effective when editing the project parameters.	Bug Fix	
Solved the crash problem caused by the name containing illegal characters when creating a new project.	Bug Fix	
After setting the latitude and longitude format	Bug Fix	

to DD:MM.MMM, the number of decimal places is changed to 7 digits.		
Solved the problem that the link and differential delay are not displayed on the survey interface when Oscar is set as the receiver network rover mode.	Bug Fix	
Solved the problem that the debug button in the device info interface sometimes is opened illegally when switching from connecting David to connecting Oscar.	Bug Fix	
Corrected the English expression of the altitude and geodetic height on the survey interface.	Bug Fix	
Corrected the English expression of long press to cancel the Bluetooth match on the connection interface.	Bug Fix	
The display of base point coordinates is changed to ground when base antenna height is obtained.	Enhancement	2.0.1.4
The display of north / east direction STD is added to the survey point attribute which is allowed to be exported.	Enhancement	
During the point survey process, it is allowed to stop the survey by pressing the stop button.	Enhancement	
Fixed the issue that after configuring David by Nuwa to stop the base mode, restarting David it still displays as Base.	Bug Fix	
Fixed the probabilistic crash issue of returning to the main interface after completing the	Bug Fix	

point staking.		
Open Oscar Reset function	Enhancement	2.0.1.2
The Collection End time of points in the point library will change with the software time zone setting	Enhancement	
The project list is arranged in reverse chronological order by edit time	Enhancement	
Fixed crash caused by choosing an empty coordinate system	Bug Fix	
Fixed the probabilistic crash in NFC connection	Bug Fix	
Fixed the probabilistic crash of setting Ntrip server after Oscar connection	Bug Fix	
Fixed failure of setting up TCPClient in connecting David	Bug Fix	
Solved the problem that modifying antenna parameters does not take effect after the survey of smooth points is completed	Bug Fix	
Solved the problem that Base points would not increase after reaching 9	Bug Fix	
Fixed HTML export crash when there are stakepoints	Bug Fix	
Solved the problem that the export Collection End time property has no hour, minute, or second, when the separator is a space in custom export	Bug Fix	
Solved the problem that the searched results for the point library based on time is empty	Bug Fix	
Fix the severe problem that modification of Ant Height is not effective in the Survey Config	Bug Fix	2.0.0.9

Supports new model Oscar	Enhancement	2.0.0.8
Added display of base shift, datum transition, plane adjustment and height fitting in the interface of Satellite Info - Position	Enhancement	
For data import, it supports data preview before importing data	Enhancement	
For data export, it added HTML export	Enhancement	
Custom import and export format support editing, viewing and deleting	Enhancement	
Added related tips in the Bluetooth pairing and device connection interface	Enhancement	
The base supports RTCM3.0 format	Enhancement	
The logic of Detailed Point acquisition is modified to pop up confirmation dialogue after the acquisition is completed	Enhancement	
Added threshold distance setting for stakeout tone	Enhancement	
In the survey configuration - Display configuration interface, added the check box of displaying all stake out points	Enhancement	
Solve the flashback problem of Nuwa in landscape orientation display	Bug Fix	
Unify NEh coordinates and RMS data, retain 4 decimal places	Bug Fix	
Solve the application crash caused by the special registration date in the Demo Key	Bug Fix	
Solve the problem of incomplete display of part of the Spanish interfaces	Bug Fix	
Solve the problem that the seven parameters	Bug Fix	

and the correction parameters are not imported into the project parameters in the newly created project		
Solve the problem of search failure according to time in point library search	Bug Fix	
Solve the problem that exporting the custom interface cannot slide	Bug Fix	
Solve the problem that in the survey interface the speed is not refreshed	Bug Fix	
Adjust default antenna	Bug Fix	
Added Japanese JGD2011 coordinate system	Enhancement	1.0.9.7
Optimized the stakeout prompt message	Enhancement	
Fixed the problem of wrong name for the Portugal coordinate system	Bug Fix	1.0.9.5
Fixed the problem of inaccurate acquisition time during the point collection	Bug Fix	
Optimized the SHP export coordinate format	Enhancement	
Optimized online upgrade information prompts	Enhancement	
Optimized Tools Offset Point calculation	Enhancement	
Optimized Tools Azimuth and Intersection Angle calculation	Enhancement	
Optimized OSM online map loading	Enhancement	
Optimized the seven parameters calculation	Enhancement	
Optimized Survey Config options	Enhancement	
Optimized the function of adding stakeout points and control points	Enhancement	
Added Ghana's predefined coordinate system	Enhancement	
Added Portuguese predefined coordinate	Enhancement	1.0.8.0

Information and related materials are subject to change without notice. ©Copyright 2019 Tersus GNSS Inc.

Technical Support: [support@tersus-gnss.com](mailto:support@tersus-gnss.com) Website: [www.tersus-gnss.com](http://www.tersus-gnss.com)

system		
Optimized static storage	Enhancement	
Optimized elevation fitting calculation	Enhancement	
Fixed elevation problems caused by geoid model during data inverse calculation	Bug Fix	
Fixed the flashback issue caused in certain situations	Bug Fix	
Optimize DXF export	Enhancement	
Fixed the problem that the default is the control point library when importing points for stakeout point library	Bug Fix	
Fixed the problem that the interface has no prompt when the stakeout point is approaching the stakeout point library	Bug Fix	
Support collecting points with physical collection button in TC20 controller	Enhancement	1.0.4.1
Support quick points collecting in 'point stakeout' and 'line stakeout' with physical collection button	Enhancement	
Add 'survey hotkey' in point survey configuration page	Enhancement	
Fix average collection problem if the solution can't meet the requirements	Bug Fix	
Change the display of coordinate axis in projection parameters as X->North Y->East	Enhancement	
Optimized the calculation of parameters and the secondary calculation process of point correction	Enhancement	1.0.3.3
Optimized the device connection experience	Enhancement	



Optimized the device registration experience	Enhancement	
Optimized antenna management	Enhancement	
In the survey configuration, the survey epoch is changed to be editable by users	Enhancement	
Added Oscar preview in Device Connection, so stay tuned! !	Enhancement	
Added support for common NMEA devices	Enhancement	1.0.3.2
Added the function of automatically zooming the scale when approaching the stakeout point during point stakeout/line stakeout	Enhancement	
Added multi-point selection function when importing stakeout points	Enhancement	
Solved the connection stability of NtripClient function under Spanish and other languages	Enhancement	
Added the functions of Device Debug and static mutual exclusion	Enhancement	
Fixed the display problem when NtripClient and TCPClient are connected	Bug Fix	
Modified the GNSS point coordinates displayed in the base shift as BLH	Enhancement	
Optimized static record Station ID setting function	Enhancement	
Fixed crash when switching languages in Spanish and other languages	Bug Fix	
Combined the mount point and rover configuration to solve the problem of the display of the mount point history data	Enhancement	
Fixed the problem that the collection time epoch does not take effect in the survey	Bug Fix	

configuration		
Fixed the problem of not displaying NEh coordinates when manually starting the base station	Bug Fix	
Fixed the problem that the base point cannot be selected in the base shift	Bug Fix	
Fix the stakeout point error on the map and coordinates error after the base shift	Bug Fix	
Fixed the error of multiple repetitive calculations in the base shift	Bug Fix	
Added support for north-south/east-west hemisphere	Enhancement	
Optimize continuous point survey by distance	Enhancement	1.0.2.9
Optimize continuous point survey by time	Enhancement	
Add the predefined coordinate systems of Malaysia and Romania	Enhancement	
Add the function of station-id setting during static measurement	Enhancement	
Add the function of Inner RTK control	Enhancement	
Add the function of importing projects	Enhancement	
Add preview function for predefined coordinate system	Enhancement	
Optimize the arrangement and display of countries or regions in the predefined coordinate systems	Enhancement	
Optimize the display of satellite quantity	Enhancement	
Optimize the display of antenna height interface	Enhancement	
‘Connected’ at the top of the main interface	Enhancement	

Information and related materials are subject to change without notice. ©Copyright 2019 Tersus GNSS Inc.

Technical Support: [support@tersus-gnss.com](mailto:support@tersus-gnss.com) Website: [www.tersus-gnss.com](http://www.tersus-gnss.com)

is changed to 'Connected'		
The position status of satellite interface for base station is changed to 'Base Manual' and 'Base Auto'	Enhancement	
Fix the problem of not displaying NEh coordinates when manually starting the base station	Bug Fix	
Add new projections: Cassini, Oblique Stereographic Alternative, Stereographic, and Transverse Cylindrical Equal Area	Enhancement	
Fix the problem of imported line files are not identified	Bug Fix	
Fix the problem of crashing when creating new projects and point survey under Spanish language	Bug Fix	
Optimize database upgrade	Enhancement	
Add predefined coordinate system	Enhancement	1.0.2.8
Modify the satellite quantity display as 'satellite tracked / satellite used'	Bug Fix	
Optimize the export format of dxf file	Enhancement	
Fix the problem that the elevation increases when manually starting the base station	Bug Fix	
Optimize base shift experience	Enhancement	
Change shp/dxf export coordinates to local coordinates	Enhancement	
Fix the problem that satellites on the Sat Tab interface has always shown true	Bug Fix	
Add differential data format display when using Ntrip to obtain source list	Enhancement	

Optimize system stability	Enhancement	1.0.2.6
System compatibility is improved, compatible with upgrades on older software	Enhancement	
Fixed the problem that the antenna height disappeared in the device connection interface after reloading the software	Bug Fix	
Fixed the problem of the invalidity of static survey after canceling auto-start	Bug Fix	
Fixed the problem of the Ntrip Client set up failure for the rover	Bug Fix	
Fixed the problem of the antenna height configuration failure for the rover	Bug Fix	
Optimize the software automatic update experience	Enhancement	
Optimize the device connections	Enhancement	
Optimize continuous acquisition by time	Enhancement	
Add Geoid Model: (1) support EGM96 and EGM08 at the same time; (2) optimize data loading and reduce waiting time for different devices; (3) simplify algorithm calculation process and save system resources	Enhancement	
Add UTM projection support for the southern hemisphere	Enhancement	
Optimize the rules for point acquisition automatic naming	Enhancement	
Optimize the base shift function: (1) support multiple times of base shift; (2) support real-time modification of the shift parameters; (3) reorganize the base shift logic; (4) redesign	Enhancement	

the base shift UI		
Optimize the solution state of the data export, which is the same as the board definition	Enhancement	
Optimize the display of the antenna height when manual-starting the base station	Enhancement	
Repair of other problems	Enhancement	
Antenna height display optimization	Enhancement	1.0.2.4
Survey configuration: display configuration optimization	Enhancement	
Re-enter static storage, status optimization	Enhancement	
Static storage antenna optimization when self-starting the base station	Enhancement	
Line stakeout 'distance' distinguishes between positive and negative	Enhancement	
Add column name for coordinate export	Enhancement	
Remove the 'Acquisition Status' of the 'Text Acquisition' interface	Enhancement	
'Smoothing' and 'Acquisition' are combined	Enhancement	
Ntrip site management: IP address display is incomplete	Bug Fix	
Click base/rover configuration without changing order	Enhancement	
Support for name modification of base/rover configuration User-defined name can be changed, the system default name cannot be changed	Enhancement	
Add reminder when creating a new project	Enhancement	
Change the logic of antenna type choosing, the antenna type must be choosing before	Enhancement	1.0.2.3

connection		
Change the default antenna height as pole height in surveying, change the default antenna height as slant height in static surveying	Enhancement	
Support choosing file type in import file	Enhancement	
Add GPS mock location	Enhancement	
Fixed the error of configuration when build a new project	Bug Fix	
Optimized the interface freeze if there are too many points in point survey interface	Enhancement	
Optimized the display of export interface	Enhancement	
Optimized the display of the result in two point intersection	Enhancement	
Optimized the display of title bar	Enhancement	
Optimized the option logic in import interface	Enhancement	
Change the voice output frequency in point stakeout	Enhancement	
Add RTCM1230 message in base model	Enhancement	
Fixed software crashed when sharing project	Bug Fix	
Optimized the logic to register David	Enhancement	
Optimized the device connection	Enhancement	
Support auto start static mode	Enhancement	
Add xyz apporoximate in rinex file	Enhancement	
Optimized the speed to log in CORS.	Enhancement	
Add point name and code in dxf format	Enhancement	1.0.2.2
Fix the abnormity H value if the antenna slant height is zero	Bug Fix	
Change the 'Projection' to 'CRS'	Enhancement	

Information and related materials are subject to change without notice. ©Copyright 2019 Tersus GNSS Inc.

Technical Support: [support@tersus-gnss.com](mailto:support@tersus-gnss.com) Website: [www.tersus-gnss.com](http://www.tersus-gnss.com)

Change the threshold value in collect points by distance	Enhancement	
Optimized auto collect function by distance	Enhancement	1.0.2.1
Optimized software access authority (it need location information authority at the same time when using Bluetooth if your android version is higher than Android 6.0)	Enhancement	
Optimized auto update function	Enhancement	
Optimized the display of system language	Enhancement	
Optimized many default value	Enhancement	
Optimized the pop-up message when getting the first fixed solution	Enhancement	
Optimized the language of pop-up messages	Enhancement	
Fixed the display error in height fitting title panel	Bug Fix	1.0.2.0
Default to open update auto test function	Enhancement	
Fixed software crash due to the display of decimal point in some language	Bug Fix	
Optimized the display of project information	Enhancement	
Fixed the bug that the QR code can't refresh when project parameters changed	Bug Fix	
Fixed the title can't be changed with system language changed	Bug Fix	
Fixed numeric keypad have no decimal point problem in some cellphone	Bug Fix	
Fixed the unusual local coordinate value under some ellipsoid	Bug Fix	