

Tersus GeoBee Item List



Receiver with Basic Accessories



1 x David GNSS Receiver



1 x Ntrip Modem TR600



1 x AX3702 GNSS Antenna



1 x TNC-J to SMA Cable ^[1]



1 x Bottom Plate for Fixing David



1 x DC-2pin AC Power Adapter with 1.2m Cable



1 x COMM2-7pin to TR600-DC-2pin & DB9 Female & USB Cable



1 x COMM1-7pin to DB9 Male Cable



1 x RS232 to RS485 Converter



1 x DB9 Female to TR600-RS485-5pin Cable



1 x USB Type A Female to USB (Micro+Type C) OTG Cable



1 x DB9 Female to USB Type A Male Converter Cable



1 x COMM1-Bluetooth Module



1 x 4G Antenna for TR600



1 x Wi-Fi Antenna for TR600




2 x Ethernet Cable 1.5m



1 x GNSS Antenna Connector



1x Travel Adapter GN901A / GN901E / GN901G / GN901N^[2]



1 x Bracket & Slide for TR600



1 x Quick Start



1 x Warranty Card



1 x Carrying Case

[1] The length of TNC-J to SMA cable is 25m by default and can be customized according to customer requirements.
[2] The model of the adapter will be delivered according to customer requirements.