

Tersus GNSS

Ntrip Modem TP688

Industrial Modem for Ntrip Corrections

Overview

The Ntrip Modem TP688 is an industrial modem ideal for Ntrip corrections. It equips built-in industrial 4G wireless communication module, built-in 2600mAh battery, RS232 serial port, mounting handle, SIM card slot and high-speed data transmission module. It is a cost-effective industrial wireless modem.

The TP688 supports Ntrip protocol, and it can be used in Ntrip server mode and Ntrip client mode. The Ntrip function is configured by RS232 serial port and text message.

Key Features

- ✓ Industrial design and IP67-rated protection
- ✓ Industrial component ARM and modules
- ✓ Serial data transfer and wide voltage input
- ✓ Low power consumption
- ✓ Long-lasting operation with built-in 2600mAh battery
- ✓ Supports global 2G/3G/4G network
- ✓ Supports DNS proxy
- ✓ Supports NTRIP
- ✓ Ease of configure, use and maintain



Tersus GNSS Ntrip Modem TP688

Technical Specifications

Performance

Input Voltage:	5V~36V DC
Operating Current:	125mA @ +12V DC
Standby Current:	90mA @ +12V DC
Power Consumption (Typical):	1.5W
Battery:	2600 mAh
Charging Time:	3.5 hours
Operating Hours (Typical):	18 hours

Physical

Dimension:	160x102x37mm (w/o connectors)
Weight:	650g
Operating Temperature:	-40°C ~ +85°C
Relative Humidity:	95% @ +40°C

Interfaces

Serial Port:	RS232 x1
Antenna Connector:	SMA Female x1
Power Connector:	2pin LEMO

Communication

<p>Network:</p> <p>Chinese version:</p> <ul style="list-style-type: none"> 2G: GSM/GPRS/EDGE/CDMA2000 1x 3G: UMTS/WCDMA/HSDPA/HSPA+/TD-SCDMA/CDMA2000 EVDO 4G: TDD-LTE/FDD-LTE <p>Eurasian version (Europe, Middle East, Africa, South Korea, Thailand):</p> <ul style="list-style-type: none"> 2G: GSM/GPRS/EDGE 3G: UMTS/WCDMA/HSDPA/HSPA+ 4G: TDD-LTE/FDD-LTE <p>North American version:</p> <ul style="list-style-type: none"> 3G: UMTS/WCDMA/HSDPA/HSPA+ 4G: FDD-LTE <p>Australian version (New Zealand, Australia, South America):</p> <ul style="list-style-type: none"> 2G: GSM 3G: WCDMA 4G: FDD-LTE/TDD-LTE
<p>Operating Frequency Band:</p> <p>Chinese version:</p> <ul style="list-style-type: none"> TDD-LTE B38/B39/B40/B41 FDD-LTE B1/B3/B8 UMTS/HSDPA/HSPA+ B1/B8 TD-SCDMA B34/B39 CDMA2000 1x/EVDO BC0 GSM/GPRS/EDGE 900/1800 MHz <p>Eurasian version:</p> <ul style="list-style-type: none"> TDD-LTE B38/B40 FDD-LTE B1/B3/B7/B8/B20 UMTS/HSDPA/HSPA+ B1/B8 GSM/GPRS/EDGE 900/1800 MHz <p>North American version:</p> <ul style="list-style-type: none"> FDD-LTE B2/B4/B5/B17 UMTS/HSDPA/HSPA+ B2/B5 <p>Australian version:</p> <ul style="list-style-type: none"> FDD-LTE B1/B2/B3/B4/B5/B7/B8/B28 TDD-LTE B40 WCDMA B1/B2/B5/B8 GSM 850/900/1800/1900

Website: www.tersus-gnss.com
Sales Inquiry: sales@tersus-gnss.com
Technical Support: support@tersus-gnss.com

Information is subject to change without notice.
 © Copyright 2023 Tersus GNSS Inc.